

## SuperQ™ 200V N-Channel Power MOSFET

### FEATURES

- Industry leading  $R_{DS(on)}$  in TOLT package
- High short-circuit withstand capability (SCWC)
- 100% UIS tested in production
- Low switching losses,  $Q_{sw}$  and  $E_{oss}$
- 175°C Industrial temperature rating

### APPLICATIONS

- Motor control
- Boost converters and SMPS control FETs
- Secondary side synchronous rectifier


### DESCRIPTION

Engineered for high-efficiency SMPS and motor drives, this 200V SuperQ MOSFET delivers ultra-low conduction and switching losses in a robust TOLT package. Featuring best-in-class  $R_{DS(on)}$  and  $Q_{sw}$ , it minimizes heat dissipation at both full and partial loads.

### PRODUCT SUMMARY



TOLT



Parameter	Value	Unit
$T_A = 25^\circ\text{C}$		
$V_{DS}$	200	V
$R_{DS(on),max}$	3.9	m $\Omega$
$I_D$	191	A
$Q_G$	133	nC
$Q_{sw}$	7.3	nC
$E_{oss}$	4.1	$\mu\text{J}$



### ORDERING INFORMATION

Part Number	Package	Marking	Packaging
iS20M3R9S1TC	TOLT	iS20M3R9S1	13" 1,300pcs T&R

### ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER ( $T_A = 25^\circ\text{C}$ unless otherwise specified)	VALUE	UNIT
$V_{GS}$	Gate-to-source voltage	$\pm 20$	V
$I_D$	Continuous drain current (silicon limited), $T_C = 25^\circ\text{C}$	191	A
	Continuous drain current (silicon limited), $T_C = 100^\circ\text{C}$	135	
$I_{DM}$	Pulsed drain current	560	A
$P_D$	Power dissipation, $T_C = 25^\circ\text{C}$	314	W
$T_J, T_{stg}$	Operating junction, storage temperature	-55 to 175	$^\circ\text{C}$
$E_{AS}$	Avalanche energy, single pulse $I_D = 60\text{A}$ , $R_{GS} = 25\Omega$	788	mJ

### THERMAL CHARACTERISTICS

SYMBOL	PARAMETER ( $T_A = 25^\circ\text{C}$ unless otherwise specified)	VALUE			UNIT
		MIN	TYP	MAX	
$R_{\theta JC}$	Junction-to-case thermal resistance - TOLT	-	-	0.5	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Junction-to-ambient thermal resistance <sup>(1)</sup>	-	-	50	$^\circ\text{C}/\text{W}$


(1) 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm (one layer, 70  $\mu\text{m}$  thick) copper area for drain connection. PCB is vertical in still air.







<b>ELECTRICAL CHARACTERISTICS</b> ( $T_A = 25^\circ\text{C}$ unless otherwise specified)						
SYMBOL	PARAMETER	TEST CONDITIONS	VALUE			UNIT
			MIN	TYP	MAX	
<b>STATIC CHARACTERISTICS</b>						
$BV_{DSS}$	Drain-to-source voltage	$V_{GS} = 0V, I_D = 1mA$	200	-	-	V
$I_{DSS}$	Drain-to-source leakage current	$V_{GS} = 0V, V_{DS} = 160V, T_J = 25^\circ\text{C}$	-	-	1	$\mu\text{A}$
		$V_{GS} = 0V, V_{DS} = 160V, T_J = 125^\circ\text{C}^{(2)}$	-	-	100	
$I_{GSS}$	Gate-to-source leakage current	$V_{DS} = 0V, V_{GS} = 20V$	-	-	100	nA
$V_{GS(th)}$	Gate-to-source threshold voltage	$V_{DS} = V_{GS}, I_D = 300\mu\text{A}$	2.6	3.4	4.2	V
$R_{DS(on)}$	Drain-to-source on-resistance	$V_{GS} = 10V, I_D = 40A$	-	3.5	3.9	m $\Omega$
$g_{fs}$	Transconductance	$V_{DS} = 10V, I_D = 40A$	40	80	-	S
<b>DYNAMIC CHARACTERISTICS</b>						
$C_{iss}$	Input capacitance <sup>(2)</sup>	$V_{GS} = 0V, V_{DS} = 100V, f = 100\text{kHz}$	-	7,974	10,366	$\text{pF}$
$C_{rss}$	Reverse transfer capacitance <sup>(2)</sup>		-	34	46	
$C_{oss}$	Output capacitance <sup>(2)</sup>		-	267	347	
$C_{o(er)}$	Effective output capacitance	$V_{DS} = 0 \text{ to } 100V, V_{GS} = 0V$	-	805	-	
$R_G$	Series gate resistance	$f = 1\text{MHz}$	-	3.5	7	$\Omega$
$t_{d(on)}$	Turn-on delay time	$V_{DS} = 100V, V_{GS} = 10V, I_{DS} = 40A,$ $R_{G,EXT} = 0\Omega$	-	TBD	-	ns
$t_r$	Rise time		-	TBD	-	
$t_{d(off)}$	Turn-off delay time		-	TBD	-	
$t_f$	Fall time		-	TBD	-	
<b>GATE CHARGE CHARACTERISTICS</b>						
$Q_G$	Gate charge total <sup>(2)</sup>	$V_{DS} = 100V, I_D = 40A,$ $V_{GS} = 0 \text{ to } 10V$	-	133	172	nC
$Q_{sw}$	Switching charge <sup>(3)</sup>		-	7.3	-	
$Q_{gd}$	Gate to drain charge <sup>(2)</sup>		-	3.4	4.4	
$Q_{g(th)}$	Gate charge at threshold		-	25	-	
$Q_{gs2}$	Gate to source charge <sup>(3)</sup>		-	3.9	-	
$V_{plateau}$	Gate plateau voltage		-	5.4	-	V
$Q_{oss}$	Output charge <sup>(2)</sup>	$V_{DS} = 0 \text{ to } 100V, V_{GS} = 0V$	-	592	770	nC
$E_{oss}$	Capacitive stored energy		-	4.1	-	$\mu\text{J}$
<b>DIODE CHARACTERISTICS</b>						
$V_{SD}$	Diode forward voltage	$I_{SD} = 40A, V_{GS} = 0V$	-	0.8	1	V
$Q_{rr}$	Reverse recovery charge	$V_{DS} = 100V, I_F = 40A,$	-	450	-	nC
$t_{rr}$	Reverse recovery time	$di/dt = 100A/\mu\text{s}$	-	110	-	ns

(2) Defined by design. Not subject to production test.




(3)  $Q_{sw}$  should be used for switching loss calculations. See  $Q_{sw}$  application note on [www.idealsemi.com](http://www.idealsemi.com)

## DEVICE DECODER RING



-  — iDEAL Semiconductor product
-  — Voltage rating divided by 10 (200V)
-  — M = N-Channel MOSFET, Standard Threshold
-  — Maximum drain-to-source resistance
-  — SuperQ™ Generation
-  — TC = TOLT

## TOLT Package Drawing



SYMBOL	MIN	MAX
A	2.20	2.35
A1	0.01	0.11
b	0.60	0.85
c	0.45	0.65
D	10.00	10.30
D1	4.76	5.87
D2	1.80	2.20
D3	2.42	2.82
D4	1.33	2.44
D5	2.08	2.48
E	9.70	10.10
E1	9.26	9.66
E2	8.10	8.50
e	1.20 BSC	
H	14.80	15.20
L	2.25	2.65
L1	1.30	1.70
P	2.90	3.10

Notes:

- All linear dimensions in millimeters

## IMPORTANT NOTICE AND DISCLAIMER

IDEAL SEMICONDUCTOR DEVICES, INC. ("IDEAL") PROVIDES THE DATASHEET AND ALL SUPPORTING DESIGN RESOURCES, SAFETY INFORMATION, AND OTHER MATERIALS (THE "RESOURCES") "AS IS". IDEAL AND/OR ITS LICENSORS DO NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE RESOURCES OR THAT SUCH RESOURCES WILL BE SUITABLE FOR YOUR APPLICATION. IDEAL HEREBY DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, OR NON-INFRINGEMENT.

You are only permitted to use the Resources and any products provided by iDEAL ("Products") in accordance with the operating parameters set forth in the Resources and iDEAL's standard terms and conditions made available at the time of order placement. Please note that the Resources are intended for skilled, technically-trained developers. You are solely responsible for, and iDEAL disclaims all responsibility and liability for: (a) choosing the Products and evaluating the suitability of such Products for the intended application, as well as determining if the information in the Resources is complete for your application; (b) designing, validating and testing the Products in your system; and (c) ensuring your application meets applicable safety, security, regulatory or other industry requirements and standards. iDEAL assumes no liability for any damage or malfunction resulting from improper handling of Products, or use of Products and Resources outside of the specified parameters. You are responsible for consulting the latest datasheet before placing orders.

iDEAL reserves the right to make corrections, modifications, enhancements, improvements and other change to or otherwise discontinue its Resources and Products in its sole discretion at any time without notice. All Products are sold subject to iDEAL's standard terms and conditions made available at the time of order placement.

Mailing Address:

iDEAL Semiconductor Devices, Inc.  
116 Research Drive  
Bethlehem, Pennsylvania, USA 18015  
[info@idealsemi.com](mailto:info@idealsemi.com)